



Artículo	R1	R2	R3	L	L1	HEX 1	HEX 2	ØC
A22240400	1/4" BSP	1/4" BSP	1/4" BSP	45	22	19	19	6
A22240600	3/8" BSP	3/8" BSP	3/8" BSP	50	24,5	22	22	8
A22240800	1/2" BSP	1/2" BSP	1/2" BSP	60	29	27	27	11
A22241200	3/4" BSP	3/4" BSP	3/4" BSP	69	34	32	32	16
A22241600	1" BSP	1" BSP	1" BSP	84	42	41	41	22

BSP		BSPT MALE		BSPP MALE		BSPP FEMALE (Crimp Nut)		BSPP FEMALE (Wire Nut)		BSPP MALE (O Ring & Retaining Ring)		BSPP MALE (Bonded seal)	
THREAD SIZE	DASH SIZE	bar	psi	bar	psi	bar	psi	bar	psi	bar	psi	bar	psi
1/8	-02	830	12000	830	12000	700	10150			420	6000	500	7250
1/4	-04	830	12000	830	12000	700	10150			420	6000	500	7250
3/8	-06	700	10150	700	10150	700	10150			420	6000	500	7250
1/2	-08	700	10150	700	10150	600	8700			420	6000	420	6000
5/8	-10	600	8700	600	8700	500	7250			280	4060	350	5100
3/4	-12	600	8700	600	8700	420	6000	500	7250	280	4060	350	5100